



BRIEF DESCRIPTION

PIERLUIGI NERI Type TRACTOR tug is specially designed to assist ships during berthing unberthing operations in port. With two SCHOTTEL azimuth thrusters, highly manoeuvrable, this tugboat has its drum towing winch located on the main deck aft, thus allowing to switch from towing to pushing within seconds. A towing hook is fitted on the main deck aft, giving an even higher operational flexibility. It offers a fire-fighting 1 (2 x 1200 cbm/hr) and REC OIL capability. The vessel is fitted with an automation for engine room, according to notation IAQ1.



MAIN CHARACTERISTICS

LOA 26,93 meters
Breadth 9.10 meters
Breadth over all 9.12 meters

Max. Draught (extreme) 5.28 meters

GRT-Net T 194,37-17,05

REGISTRATION

Type of Vessel Tractor Tug, IAQ1, Fire Fighting ship 1,Oil Recovery Ship

Year built 2002

Builder C.N. Rosetti Marino s.p.a.- Ravenna (Italy)

CALL Sign/Rina Nr IZIZ / 79471

Classification RINA 100A 1.1, IAQ1, Fi-Fi 1 Tug, National Coastal

PERFORMANCE

Speed 12,00 knots

Direct Bollard Pull 49,06 tons =481,30 KN

PROPULSION -MACHINERY

Main Engines 2 x DEUTZ_Mannheim model SBV6M628 with a power of 2 x 1260

Kw at 1000 rpm

Gen Sets 2 x DEUTZ BF6M1013 x 100 kVA 50 Hz/380 V with possibilità to

power suppli to third party

Harbour Gen Sets 1 IVECO AIFO 8035M6.2 x 24 kVA 50 Hz/400 V Propulsion Units 2 x Schottel pitch propellers in steerable kort nozzles

Propellers 2 Schottel SRP 1010 FP

ACCOMODATION

Accomodation 2 cabins for 1 officer plus spares, 4 cabin for 1 crew, total 6 persons,

mess galley, stores, WC's and showers

Airconditioning Fully airconditioned, temperatures as per ISO standards,

TOWING and SPECIAL EQUIPMENT

Fore Towing -----

winch

Aft Towing C. Kraijeveld B.V. Hydraulic towing winch type KA8-H

Winch

Hook Mampaey quick release disk type towing hook DCX 50/65

Fratelli Neri S.p.A.

Via Pisa n. 10- 57123 Livorno- ITALY Ph. +39 0586 234111- Fax +39 0586 892025 www.nerigroup.net – e mail: info@nerigroup.net



TANK CAPACITIES

Fuel Oil 109 mc Fresh Water 32,7 mc Foam 10 mc

Lub Oil MMEE

Waste Oil

Lub Oil Hydr. system

Sewage /sludge 3,5 / 6,00 mc Ballast 16,2 mc

REC OIL 30 +30 reserve

ELECTRONICS

Communication FURUNO FS 1562/15it, FURUNO FM 8500

Navigation equipment 1 radar, 1 GPS, Gyrocompass, Magnetic Compass, Auto Pilot, Echo

Sounder, AIS, Speed Log.

LIFE SAVING EQUIPMENT

1 rigid rescue boat, 2 x Liferaft for 12 persons, 8 life jackets, 2 life

buoys, line throwers, thermal suits all SOLAS approved

Solas Boat & Crane ILO Approved boat and crane.

FIRE FIGHTING SYSTEM Class FI FI 1

Nr 2 x monitors of 1200 cbm/hr capacity each

Fi-Fi 1 capacity with CounterFire Ltd system, water & foam