

GENERAL

YARD NUMBER DELIVERY DATE BASIC FUNCTIONS

CLASSIFICATION

FLAG OWNER

DIMENSIONS

LENGTH O.A. BEAM O.A. DEPTH AT SIDES DRAUGHT AFT DISPLACEMENT (98%)

TANK CAPACITIES

FUEL OIL FRESH WATER SEWAGE LUB. OIL DIRTY OIL SLUDGE BILGE WATER FOAM DISPERSANT OIL RECOVERY

PERFORMANCES

BOLLARD PULL AHEAD BOLLARD PULL ASTERN SPEED AHEAD SPEED ASTERN

PROPULSION SYSTEM

MAIN ENGINES TOTAL POWER THRUSTERS PROPELLER FORCED VENTILATION 512540 January 2016 Push-pull, escorting, towing, fire-

fighting and oil recovery operations RINA I № HULL • MACH Escort Tug; Supply

vessel; Fire Fighting ship 1 -water spraying; Oil recovery ship SECOND-LINE -flash point > 60°C -oil product Unrestricted Navigation • AUT-UMS, INWATERSURVEY Italy

Fratelli Neri S.p.A Livorno

32.70 m
12.82 m
5.35 m
5.51 m
815 ton

141.8 m³	
15.2 m ³	
5.1 m ³	
8.1 m ³	
4.3 m ³	
2.5 m ³	
6.8 m ³	
12.6 m ³	
5.4 m ³	
42.6 m ³	

80.8 ton 74.9 ton 14.3 knots 13.9 knots

2x Caterpillar 3516C HD+ TA/D 5050 bkW (6772 bhp) at 1800 rpm 2x Rolls Royce US255 P30 CP Special 2800 mm controllable pitch 20.000/40.000 m³/hr

DAMEN ASD TUG[®] 3212 "LUISA NERI"

2x Caterpillar C6.6 TA, 230/400 V, 125 kVA, 50 Hz

2x Sterling AKHA 6101 each 34 m³/hr

Sterling AKHA 5101 and AOHA 3101

Dispersant pumpset with 2 spraybooms

2x 495 kg Pool (High Holding Power)

5 ton at 15 m/min. Electrically driven

cylinder bow fenders with water spray

Hydraulically driven double drum winch

Rendering 100 ton up to 100 m/min at second layer

Recovery 60 ton up to 50 m/min at second layer

Heila HLM 20-3S + winch 1.7 ton at 10.56 m

Normal mode pull 60 ton up to 20 m/min, 200 ton

Hydraulically driven, single drum winch with spooling device and warping head, pull 30 ton up to 40 m/min

D-fender at sides, cylinder fender at transom corners,

Main engine driven pump FIFI 1 2400 m³/hr

Box cooling + anti growth system Sterling HBK 111 / AOHA 3101

Westfalia OTC 3-02-137

Main engine driven pumps

2 x 1400 m³/hr, water/foam

AUXILIARY EQUIPMENT

GENERATOR SETS BILGE PUMPS FUEL PUMPS COOLING SYSTEM FRESHWATER PRESSURE SET FUEL OIL PURIFIER HYDRAULIC SYSTEM OIL POLLUTION CONTROL FIFI SET FIFI MONITOR

DECK LAY-OUT

ANCHOR ANCHOR/RENDERING-RECOVERY WINCH

CAPSTAN CRANE TOWING HOOK AFT TOWING WINCH AFT

FENDERING

ACCOMMODATION

For 10 persons, insulated and finished with durable modern linings, acoustical Dampa ceiling in the wheelhouse, floating floors and air-conditioned. With 6 cabins, galley, mess/dayroom, switchboard room, dry store and sanitary facilities.


Mampaey SWL 100 ton

and 200 ton brake

NAUTICAL AND COMMUNICATION EQUIPMENT

brake

SEARCHLIGHTS RADAR SYSTEM COMPASS GYRO COMPASS AUTOPILOT GPS ECHOSOUNDER VHF NAVTEX AIS SSB SPEED LOG INMARSAT EPIRB SART 2x 450 W Xenon (FIFI 1) Furuno FAR 2117 Magnetic Kotter Anschuetz Compact 22 Robertson AP-70 Furuno GP-150D Furuno FE-800 2x Sailor 6222 + 2x hand-held Furuno NX-700A Furuno FA-150 Furuno FA-150 Furuno FS-1575 Furuno DS-80 2x Furuno FBcom 18 Jotron TRON-40S Jotron TRONSART20



DAMEN ASD TUG[®] 3212



DAMEN SHIPYARDS GORINCHEM

Industrieterrein Avelingen West 20 4202 MS Gorinchem P.O. Box 1 4200 AA Gorinchem The Netherlands phone +31 (0)183 63 99 11

+31 (0)183 63 21 89

Member of the DAMEN SHIPYARDS GROUP

info@damen.com www.damen.com

Ð

© No part of the leaflet may be reproduced in any form, by print, photo print, microfilm, or any other means, without written permission from Damen Shipyards Gorinchem

fax